

Warranty Certificate for Shoto Lithium-ion Battery

Shuangdeng Group Co., Ltd (hereinafter referred to as SHOTO) is pleased to offer **10 years of warranty** (date from bill of lading) in telecom application for SDA10 series batteries power system under the following terms and conditions:

1. The temperature in the cabinet should be in the range of 15 to 30 degree Celsius.
2. The battery can be used for floating or cyclic scenarios. The number of discharge shall not more than 200 times per year, and the cumulative depth of discharge shall not more than 80% per day.
3. The charge parameter settings should be as under:
 - Floating Charge: 54V
 - Boost Charge : 54.5V
 - Parameters not claimed here shall be set in accordance with requirements of User Manual and Product Specification of SHOTO
4. The battery should be recharged within 48 hours after each discharge. For a fully discharged battery, if it is not be recharged for more than 72 hours, it will shorten the battery service life, so we will not provide a warranty if this case happens more than 3 times.
5. SHOTO would replace the battery during warranty period based on faulty block but not as all batteries in site.
6. SHOTO should not be held responsible for any physical damage, improper installation, handling and damage caused by any disaster.
7. SHOTO guarantees that the battery remaining capacity is more than 60% its rated capacity within the warranty period.
8. SHOTO suggests that user should keep and provide the following monthly logs if possible:
 - Number of cycles, duration of each time, the end voltage of discharge, and other recorded data.
 - Ambient and battery surface temperature.
 - The data that buyer thinks is necessary.
9. Any storage and maintenance of this battery should refer to SHOTO's User Manual.
10. The warranty period starts from the date of delivery from factory. This date can be

read from the battery's serial number.

11. Warranty claims must inform SHOTO within 1 months of battery failure. The buyer must cooperate to provide the operating temperature and parameter settings and history logs and so on. If necessary, the buyer should cooperate with our technical engineer to check on site.