

Single Phase Hybrid Inverter

SUN-3K-SG06LP1-24-EU-CM1

SUN-3K-SG06LP1-EU-CM1

SUN-3.6/4/4.6/5/6K-SG06LP1-EU-CM2



Colorful touch LCD, IP65 protection degree



AC couple to retrofit existing solar system



Max. 16 pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel



Max. charging/discharging current of 140A



6 time periods for battery charging/discharging



Support storing energy from diesel generator



Technical Data

Model	SUN-3K-SG06 LP1-24-EU-CM1	SUN-3K-SG06 LP1-EU-CM1	SUN-3.6K-SG06 LP1-EU-CM2	SUN-4K-SG06 LP1-EU-CM2	SUN-4.6K-SG06 LP1-EU-CM2	SUN-5K-SG06 LP1-EU-CM2	SUN-6K-SG06 LP1-EU-CM2
Battery Input Data							
Battery Type	Lead-acid or Lithium-ion						
Battery Voltage Range (V)	20-30	40-60					
Max. Charging Current (A)	140	70	90	95	120	120	135
Max. Discharging Current (A)	140	70	90	95	120	120	135
Charging Strategy for Li-ion Battery	Self-adaption to BMS						
Number of Battery Input	1						
PV String Input Data							
Max. PV Access Power (W)	6000	7200	8000	9200	10000	12000	
Max. PV Input Power (W)	4800	5760	6400	7360	8000	9600	
Max. PV Input Voltage (V)	500						
Start-up Voltage (V)	125						
MPPT Voltage Range (V)	150-425						
Rated PV Input Voltage (V)	370						
Max. Operating PV Input Current (A)	18	18+18					
Max. Input Short-Circuit Current (A)	27	27+27					
No. of MPP Trackers/ No. of Strings MPP Tracker	1/1	2/1+1					
AC Input/Output Data							
Rated AC Input/Output Active Power (W)	3000	3600	4000	4600	5000	6000	
Max. AC Input/Output Apparent Power (VA)	3300	3960	4400	4600	5500	6600	
Rated AC Input/Output Current (A)	13.7/13.1	16.4/15.7	18.2/17.4	21.0/20	22.8/21.8	27.3/26.1	
Max. AC Input/Output Current (A)	15/14.4	18/17.3	20/19.2	21.0/20	25.0/24.0	30/28.7	
Max. Continuous AC Passthrough (grid to load) (A)	50						
Peak Power (off-grid) (W)	2 times of rated power, 10s						
Power Factor Adjustment Range	0.8 leading to 0.8 lagging						
Rated Input/Output Voltage/Range (V)	220/230V 0.85Un-1.1Un						
Rated Input/Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65						
Grid Connection Form	L+N+PE						
Total Current Harmonic Distortion THDi	<3% (of nominal power)						
DC Injection Current	<0.5% In						
Efficiency							
Max. Efficiency	97.6%						
Euro Efficiency	96.5%						
MPPT Efficiency	>99%						
Equipment Protection							
Integrated	DC Reverse Polarity Protection, AC Output Overcurrent Protection, Thermal Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, DC Component Monitoring, Arc Fault Circuit Interrupter (optional), Anti-islanding Protection, DC Switch, Insulation Impedance Detection, Residual Current Detection						
Surge Protection Level	TYPE II(DC), TYPE II(AC)						
Interface							
LCD/LED Display	LCD						
Communication Interface	WIFI,RS485,CAN						
General Data							
Operating Temperature Range (°C)	-40 to +60°C, >45°C Derating						
Permissible Ambient Humidity	0-100%						
Permissible Altitude	3000m						
Noise (dB)	<45dB						
Ingress Protection(IP) Rating	IP 65						
Inverter Topology	Non-Isolated						
Over Voltage Category	OVC II(DC), OVC III(AC)						
Cabinet Size (WxHxD mm)	310×460×218(Excluding Connectors and Brackets)						
Weight (kg)	15.6						
Type of Cooling	natural cooling						
Warranty	5 Years/10 Years the Warranty Period Depends the Final Installation Site of Inverter, More Info Please Refer to Warranty Policy						
Grid Regulation	IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UNE 217002, OVE-Richtlinie R25, G99, VDE-AR-N 4105						
Safety / EMC Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2						